




SPYRO CERAMIC  
THE PEOPLE'S CHOICE



DISCOVER A WORLD OF INFINITE POSSIBILITIES  
WITH ENDLESS CARVING.

600  
X1200MM

EN $\infty$ ESS  
CARVING

# IT'S ALL ABOUT US

Spyro is a Group Venture by Spyro Ceramic which is renowned brands of the ceramic industry, bringing together the best of expertise and experience of more than six years. Avalta aims to revolutionize the industry by introducing never-before seen tiles that are sure to raise the bar of grandeur a notch higher.

Exclusivity in design and exquisite finishes defines the Avalta as Best products offerings. Use of quality certified raw materials and innovative - modern technology, Tiles produces in Avalta are the best blend of stylish designs and productive long lasting strength. With the newfangled ideas, we assure and able to create consolidation of Beauty, Style & Quality in Vitrified Tiles which will drive you to the luxuries way...

## **MISSION**

Willingness towards the enhancement of life style and passionately strive to delight every customer of SPYRO by providing innovative and quality products and services as ongoing basis and to become a most sought after brand.

## **VISION**

SPYRO Ceramic is committed to providing technologically-advanced, aesthetically designed, high-strength, premium quality vitrified tiles that satisfy commercial as well residential customer needs in domestic and international markets.



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE



SPYRO CERAMIC  
THE PEOPLE'S CHOICE

EN<sup>∞</sup>ESS  
CARVING

A L L N E W S E R I E S

SIZE

600x1200mm


THICKNESS  
9MM

FINISH  
CARVING

Endless carving could be interpreted in various ways depending on the context. Here are a few possible interpretations.

Style Your  
Living  
Tile With  
Endless






CERA WHITE



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

| **600x1200MM** | **CARVING** | RANDOM- **04** |




DESIGN: **CERA WHITE**

**EN<sup>∞</sup>ESS**  
CARVING



CERA WHITE



CONT GREY



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

**600x1200MM** | **CARVING** | RANDOM- **04**




DESIGN: **CONT GREY**

**EN<sup>∞</sup>ESS**  
CARVING



CONT GREY




CONT SILVER



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

| **600X1200MM** | **CARVING** | RANDOM- **04** |




DESIGN: **CONT SILVER**

**EN<sup>∞</sup>ESS**  
CARVING



CONT SILVER



DUCTO GREY



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

| **600X1200MM** | **CARVING** | RANDOM- **04** |




DESIGN: **DUCTO GREY**

**EN<sup>∞</sup>ESS**  
CARVING



DUCTO GREY




ECES DARK GREY



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

**600x1200MM** | **CARVING** | RANDOM- **04**




DESIGN: **ECES DARK GREY**

**EN<sup>∞</sup>ESS**  
CARVING



ECES DARK GREY



ECES SILVER



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

| **600X1200MM** | **CARVING** | RANDOM- **04** |




DESIGN: **ECES SILVER**

**EN<sup>∞</sup>ESS**  
CARVING



ECES SILVER




EMIUM GOLD



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

| **600X1200MM** | **CARVING** | RANDOM- **04** |




DESIGN: **EMIUM GOLD**

**EN<sup>∞</sup>ESS**  
CARVING



EMIUM GOLD



FIRMA BLUE



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

| **600x1200MM** | **CARVING** | RANDOM- **04** |




DESIGN: **FIRMA BLUE**

**ENOESS**  
CARVING



FIRMA BLUE




LES CREMA



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

**600x1200MM** | **CARVING** | RANDOM- **04**




DESIGN: **LES CREMA**

**EN∞ESS**  
CARVING



LES CREMA



LES GREY



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

| **600x1200MM** | **CARVING** | RANDOM- **04** |




DESIGN: **LES GREY**

**EN<sup>∞</sup>ESS**  
CARVING



LES GREY



LES SILVER



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

| **600X1200MM** | **CARVING** | RANDOM- **04** |




DESIGN: **LES SILVER**

**EN<sup>∞</sup>ESS**  
CARVING



LES SILVER



RISE GREY



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

**600x1200MM** | **CARVING** | RANDOM- **04**




DESIGN: **RISE GREY**

**EN<sup>∞</sup>ESS**  
CARVING



RISE GREY




TING MULTI



SPYRO CERAMIC  
THE PEOPLE'S CHOICE

600X1200MM | CARVING | RANDOM- 04



DESIGN: TING MULTI

ENOESS  
CARVING



TING MULTI

# Technical Specifications.

| CHARACTERISTIC                         | STANDARD AS PER ISO-13006/EN 14411 GROUP BIa | MEAN VALUE OF POLISHED GVT | MEAN VALUE OF GVT / PGVT    | TEST METHOD  |
|--|--|----------------------------|-----------------------------|--------------|
| REGULATORY PROPERTIES                  |  |                            |                             |              |
| Deviation in length & width            | ±0.5 %                                       | ±0.1 %                     | ±0.1 %                      | ISO-10545-2  |
| Deviation in thickness                 | ±5.0 %                                       | ±4.0 %                     | ±4.0 %                      | ISO-10545-2  |
| Straightness in side                   | ±0.5 %                                       | ±0.1 %                     | ±0.1 %                      | ISO-10545-2  |
| Rectangularity                         | ±0.5 %                                       | ±0.1 %                     | ±0.1 %                      | ISO-10545-2  |
| Surface flatness                       | ±0.5 %                                       | ±0.2 %                     | ±0.2 %                      | ISO-10545-2  |
| Color dierence                         | Unaltered                                    | No change                  | No change                   | ISO-10545-16 |
| Glossiness                             | As per mfg                                   | Min 90%                    | Min 4%                      | GLOSSOMETER  |
| STRUCTURAL PROPERTIES                  |  |                            |                             |              |
| Water absorption                       | < 0.50 %                                     | < 0.20 %                   | < 0.20 %                    | ISO-10545-3  |
| Apparent density                       | > 2.0 g/cc                                   | >2.10 g/cc                 | >2.10 g/cc                  | DIN 51082    |
| MASSIVE MECHANICAL PROPERTIES          |  |                            |                             |              |
| Modulus Of Rupture                     | Min. 35 N/mm²                                | Min. 40 N/mm²              | Min. 40 N/mm²               | ISO-10545-4  |
| Breaking strength                      | Min. 1300 N                                  | Min. 2000 N                | Min. 2000 N                 | ISO-10545-4  |
| Impact resistance                      | As per mfg                                   | Min. 0.55                  | Min. 0.55                   | ISO-10545-5  |
| SURFACE MECHANICAL PROPERTIES          |  |                            |                             |              |
| Surface abrasion resistance            | As per mfg                                   | Min. Class-3               | Min. Class-4                | ISO-10545-7  |
| MOH's hardness                         | As per mfg                                   | Min. 4                     | Min. 5                      | EN 101       |
| THERMO HYDROMETRIC PROPERTIES          |  |                            |                             |              |
| Frost resistance                       | No damage                                    | No damage                  | No damage                   | ISO-10545-12 |
| Thermal shock resistance               | No damage                                    | No damage                  | No damage                   | ISO-10545-9  |
| Moisture expansion                     | Nil  | Nil                        | Nil                         | ISO-10545-10 |
| Thermal expansion(COE)                 | Max. 9.0 x 10 <sup>-6</sup>                  | Max. 6.5x10 <sup>-6</sup>  | Max. 6.5 x 10 <sup>-6</sup> | ISO-10545-8  |
| Crazing resistance                     | As per mfg.                                  | Min. 10 Cycle              | Min. 10 Cycle               | ISO-10545-11 |
| CHEMICAL PROPERTIES                    |  |                            |                             |              |
| Chemical resistance                    | No damage                                    | No damage                  | No damage                   | ISO-10545-13 |
| Stain resistance                       | Resistant                                    | Resistant                  | Resistant                   | ISO-10545-14 |
| SAFETY PROPERTIES                      |  |                            |                             |              |
| Slip resistance                        | As per mfg.                                  | >0.40                      | >0.40                       | ISO-10545-17 |
| Fire resistance                        | As per mfg.                                  | Fire proof                 | Fire proof                  | N. A.        |
| Lead & Cadmium given o by glazed tiles | As per mfg.                                  | Does not yield Pb & Cd     | Does not yield Pb & Cd      | ISO-10545-15 |

## Packing Details.

| SR. NO. | PRODUCT         | NOMINAL SIZE  | TILES PER BOX | COVERAGE AREA |
|---------|-----------------|---------------|---------------|---------------|
| 1       | VITRIFIED TILES | 600 x 1200 mm | 2             | 1.44 Sq. Mtr. |

**Note:** •Colour Shown are as accurate as the limitations of the printing process will allow. •Prospective customers are advised to inspect a sample of the tile before ordering. • Every effort has been made to ensure the accuracy of the information given. •However, the company reserve the right to change the specifications without prior notice. •Sometime variations in shade or size being inherent to ceramic industry may occur. •Before fixing, we advise you to follow the fixing instructions on the cartons of the tiles as no responsibility can be accepted by the company once the tiles have been fixed.



SPYRO CERAMIC  
THE PEOPLE’S CHOICE



**SPYRO CERAMIC**  
THE PEOPLE'S CHOICE

spyroceramic@gmail.com | +918758844000